



SAFETY DATA SHEET

Ltd. AUTOSTIC ADHESIUM - MACHINE MOUNTING COMPOUND

Page: 1

Compilation date: 08/03/2011

Revision date: 19/04/2016

Revision No: 10

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: AUTOSTIC ADHESIUM - MACHINE MOUNTING COMPOUND

CAS number: 1344-09-8

EINECS number: 215-687-4

Product code: FF152

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Inorganic Machine Mounting Adhesive Cement

1.3. Details of the supplier of the safety data sheet

Company name: Minkon Ltd
Tofts Farm Industrial Estate
Brenda Road
Hartlepool
TS25 2BS
United Kingdom

Tel: +44 (0) 1429 273 252

Fax: +44 (0) 1429 232 611

Email: enquiries@minkon.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0) 7970 462234

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: This product has no classification under CHIP.

Classification under CLP: This product has no classification under CLP.

2.2. Label elements

Label elements under CLP:

Precautionary statements: P280: Wear eye protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Label elements under CHIP:

Hazard symbols: No significant hazard.

Safety phrases: S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

[cont...]

SAFETY DATA SHEET

AUTOSTIC ADHESIUM - MACHINE MOUNTING COMPOUND

Page: 2

Precautionary phrases: Restricted to professional users.

2.3. Other hazards

Other hazards: All the alkali silicates, even those that are not classified as Dangerous Substances, are alkaline chemicals. Therefore contact with eyes, skin and clothes should be avoided and the usual procedures for handling all chemicals should be followed.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Non-classified ingredients:

SILICIC ACID, SODIUM SALT, MOLAR RATIO >3.2 - REACH registered number(s): 01-2119448725-31-0000

EINECS	CAS	CHIP Classification	CLP Classification	Percent
215-687-4	1344-09-8	-	-	>90%

Contains: Sodium/Potassium Silicate Solution, Molar Ratio >3.2, Solids <40%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear protective clothing to prevent contact with skin and eyes.

[cont...]

SAFETY DATA SHEET

AUTOSTIC ADHESIUM - MACHINE MOUNTING COMPOUND

Page: 3

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid contact with eyes and skin. Eye wash facilities should be readily available. Wear suitable protective equipment. See Section 8 - Personal Protection. General good safety practices should be followed in the handling and use of this product. NO SMOKING OR EATING OR DRINKING should be allowed in areas of storage or use.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): PC1: Adhesives, sealants.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure good work practices. Wash splashes immediately. DO NOT eat, drink or smoke in the workplace.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

[cont...]

SAFETY DATA SHEET

AUTOSTIC ADHESIUM - MACHINE MOUNTING COMPOUND

Page: 4

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Red-brown

Odour: Odourless

Evaporation rate: Slow

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Binder soluble in water, felt non-soluble

Viscosity: Viscous

Relative density: 1.2-1.6

pH: >11.0

VOC g/l: 0

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

10.5. Incompatible materials

Materials to avoid: The product contains a water based alkaline binder, and the wet adhesive as supplied (i.e. the adhesive is in liquid form) will react readily with acids.

10.6. Hazardous decomposition products

Haz. decomp. products: Not applicable.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
-------	---------	------	-------	-------

[cont...]

SAFETY DATA SHEET

AUTOSTIC ADHESIUM - MACHINE MOUNTING COMPOUND

Page: 5

ORL	RAT	LD50	1600-3200	mg/kg
-----	-----	------	-----------	-------

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Because of the alkalinity, it is recommended that this material is classified as hazardous waste under EEC Directive 91/689/EEC.

Waste code number: EWC 060299

Disposal of packaging: Contaminated containers must be completely emptied. Discharge of this product to sewage treatment works is dependent on local regulations with regard to pH controls. Due to its alkalinity, it is recommended that this product is classified as hazardous waste under EEC Directive 91/689/EEC (and amendments).

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

[cont...]

SAFETY DATA SHEET

AUTOSTIC ADHESIUM - MACHINE MOUNTING COMPOUND

Page: 6

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: All the alkali silicates, even those that are not classified as Dangerous Substances, are alkaline chemicals. Therefore contact with eyes, skin and clothes should be avoided and the usual procedures for handling all chemicals should be followed.

Shelf life - 24 months

This product is ROHS compliant.

This product is a water based adhesive cement - VOC Content 0 gram/litre

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.