



## SAFETY DATA SHEET

FORTAFIX HT1100 FLUESEAL - HIGH TEMPERATURE FLUE SEALANT

Page: 1

Compilation date: 19/05/2010

Revision date: 19/04/2016

Revision No: 4

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** FORTAFIX HT1100 FLUESEAL - HIGH TEMPERATURE FLUE SEALANT  
**EINECS number:** 215-687-4  
**Product code:** FF114

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** High temperature resistant inorganic adhesive.

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** Minkon Ltd  
Tofts Farm Industrial Estate  
Brenda Road  
Hartlepool  
TS25 2BS  
United Kingdom  
**Tel:** +44 (0) 1429 273 252  
**Fax:** +44 (0) 1429 232 611  
**Email:** [enquiries@minkon.co.uk](mailto:enquiries@minkon.co.uk)

#### 1.4. Emergency telephone number

**Emergency tel:** +44 (0) 7970 462234

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CHIP:** This product has no classification under CHIP.

**Classification under CLP:** This product has no classification under CLP.

#### 2.2. Label elements

##### Label elements under CLP:

**Precautionary statements:** P262: Do not get in eyes, on skin, or on clothing.  
P280: Wear eye protection.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+313: If eye irritation persists: Get medical advice/attention.

##### Label elements under CHIP:

**Hazard symbols:** No significant hazard.  
**Safety phrases:** S25: Avoid contact with eyes.

[cont...]

# SAFETY DATA SHEET

FORTAFIX HT1100 FLUESEAL - HIGH TEMPERATURE FLUE SEALANT

Page: 2

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S27/28: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.

## 2.3. Other hazards

**Other hazards:** Alkaline Solution. Irritating to skin. Risk of serious damage to eyes. All the alkali silicates, even those that are not classified as Dangerous Substances, are alkaline chemicals. Therefore contact with eyes, skin and clothes should be avoided and the usual procedures for handling all chemicals should be followed.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

**Contains:** Alkaline Silicate Glass Solution.

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Do not induce vomiting. Wash out mouth with water. Drink 1 or 2 glasses of water or milk. Seek Medical Attention.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Seek Medical Attention.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** Alkaline material which may cause caustic burns to eyes.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

### 4.3. Indication of any immediate medical attention and special treatment needed

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Not Applicable. Aqueous Solution. Non Combustible. Suitable extinguishing media for the surrounding fire should be used.

### 5.2. Special hazards arising from the substance or mixture

[cont...]

# SAFETY DATA SHEET

FORTAFIX HT1100 FLUESEAL - HIGH TEMPERATURE FLUE SEALANT

Page: 3

## 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Wear Appropriate Protective Clothing. Wear Suitable Eye Protection. Material can create slippery conditions underfoot.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. If material enters drains, dilute as much as possible with water and notify the authorities.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a suitable container. Refer to section 13 of SDS for suitable method of disposal.

### 6.4. Reference to other sections

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid contact with eyes and skin. Eye wash facilities should be readily available. Wear suitable protective equipment. See Section 8 - Personal Protection. General good safety practices should be followed in the handling and use of this product. NO SMOKING OR EATING OR DRINKING should be allowed in areas of storage or use.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in cool, well ventilated area. Storage temperature should be below 50 C. Prevent from freezing. Avoid incompatible materials and conditions - see section 10 of SDS.

**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Workplace exposure limits:** No data available.

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Local exhaust ventilation if solution is sprayed. Ensure good work practices. Wash splashes immediately. DO NOT eat, drink or smoke in the workplace.

[cont...]

# SAFETY DATA SHEET

FORTAFIX HT1100 FLUESEAL - HIGH TEMPERATURE FLUE SEALANT

Page: 4

**Respiratory protection:** Respiratory protection is required if solution is sprayed. Consult British Standards BS2091 and BS4275 and HSE publication HS(G)53 for further advice on respiratory protective equipment.

**Hand protection:** Gloves (alkali-resistant).

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** PVC apron.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Paste

**Colour:** Dark grey

**Odour:** Odourless

**Evaporation rate:** Slow

**Oxidising:** Non-oxidising (by EC criteria)

**Solubility in water:** Binder soluble in water/filler insoluble

**Viscosity:** Viscous

**Relative density:** 1.5-2.5

**pH:** >11.0

**VOC g/l:** 0

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Not applicable.

### 10.4. Conditions to avoid

### 10.5. Incompatible materials

**Materials to avoid:** Strong acids. The product contains a water based alkaline binder, and the wet adhesive as supplied (i.e. the adhesive is in liquid form) will react readily with acids.

### 10.6. Hazardous decomposition products

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

[cont...]

# SAFETY DATA SHEET

FORTAFIX HT1100 FLUESEAL - HIGH TEMPERATURE FLUE SEALANT

Page: 5

## Toxicity values:

Route	Species	Test	Value	Units
ORL	RAT	LD50	1600-3200	mg/kg

## Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** Alkaline material which may cause caustic burns to eyes.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** Soluble Silicates upon dilution rapidly depolymerise into molecular species indistinguishable from natural dissolved silica.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data available.

### 12.4. Mobility in soil

**Mobility:** Soluble silicates, upon dilution, rapidly depolymerise into molecular species indistinguishable from natural dissolved silica. The alkalinity of this material will have a local effect on ecosystems sensitive to changes in pH.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** No data available.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Because of the alkalinity, it is recommended that this material is classified as hazardous waste under EEC Directive 91/689/EEC.

**Waste code number:** EWC 060299

**Disposal of packaging:** Contaminated containers must be completely emptied. Dispose of empty packaging to a place authorised to accept builders' waste (non-hazardous materials landfill).

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

[cont...]

# SAFETY DATA SHEET

FORTAFIX HT1100 FLUESEAL - HIGH TEMPERATURE FLUE SEALANT

Page: 6

## Section 14: Transport information

**Transport class:** This product does not require a classification for transport.

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

## Section 16: Other information

### Other information

**Other information:** All the alkali silicates, even those that are not classified as Dangerous Substances, are alkaline chemicals. Therefore contact with eyes, skin and clothes should be avoided and the usual procedures for handling all chemicals should be followed.

Shelf life - 12 months

This product is ROHS compliant.

This product is a water based adhesive cement - VOC Content 0 gram/litre

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.