

SAFETY DATA SHEET

HT FLEXSEAL 350 - FORTAFIX HIGH TEMPERATURE
RTV SILICONE ADHESIVE/SEALANT

Page: 1

Compilation date: 19/05/2010

Revision date: 19/04/2016

Revision No: 6

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: HT FLEXSEAL 350 - FORTAFIX HIGH TEMPERATURE RTV SILICONE
ADHESIVE/SEALANT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Red, smooth paste supplied in a cartridge, to be used as RTV sealant providing high temperature-resistant, flexible bonding.

1.3. Details of the supplier of the safety data sheet

Company name: Minkon Ltd
Tofts Farm Industrial Estate
Brenda Road
Hartlepool
TS25 2BS
United Kingdom
Tel: +44 (0) 1429 273 252
Fax: +44 (0) 1429 232 611
Email: enquiries@minkon.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0) 7970 462234

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xi: R36/38

Classification under CLP: Skin Corr. 1B: H314

Most important adverse effects: Irritating to eyes and skin.

2.2. Label elements

Label elements under CLP:

Hazard statements: H314: Causes severe skin burns and eye damage.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion



SAFETY DATA SHEET

HT FLEXSEAL 350 - FORTAFIX HIGH TEMPERATURE
RTV SILICONE ADHESIVE/SEALANT

Page: 2

Precautionary statements: P260: Do not breathe vapours.
P264: Wash hands thoroughly after handling.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.
Rinse skin with water.
P501: Dispose of contents/container to local regulations.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310: Immediately call a POISON CENTER or doctor.

Label elements under CHIP:

Hazard symbols: Irritant.



Risk phrases: R36/38: Irritating to eyes and skin.

2.3. Other hazards

Other hazards: Liberates a small amount of acetic acid on curing which may be irritating to eyes, skin and respiratory system.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ZZ ARCHIVE - RAW MATERIAL - ETHYLTRIACETOXYSILANE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	17689-77-9	-: R14; C: R34	-	1-10%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.

Eye contact: Remove contact lenses Bathe the eye with running water for 15 minutes. Obtain medical attention if symptoms develop.

Ingestion: Wash out mouth with water. Seek medical attention if irritation persists.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Keep warm and at rest. Seek medical attention if irritation persists.

[cont...]

SAFETY DATA SHEET

HT FLEXSEAL 350 - FORTAFIX HIGH TEMPERATURE
RTV SILICONE ADHESIVE/SEALANT

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Do not handle in a confined space. Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

[cont...]

SAFETY DATA SHEET

HT FLEXSEAL 350 - FORTAFIX HIGH TEMPERATURE
RTV SILICONE ADHESIVE/SEALANT

Page: 4

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure good work practices. Wash splashes immediately. DO NOT eat, drink or smoke in the workplace.

Respiratory protection: Respiratory protective device with particle filter. Half Face Respirator ReadyPak A2P2

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Dark red

Odour: Acetic acid

Evaporation rate: Negligible

Solubility in water: Insoluble

Viscosity: Thixotropic

Relative density: 1.29

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

[cont...]

SAFETY DATA SHEET

HT FLEXSEAL 350 - FORTAFIX HIGH TEMPERATURE
RTV SILICONE ADHESIVE/SEALANT

Page: 5

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

[cont...]

SAFETY DATA SHEET

HT FLEXSEAL 350 - FORTAFIX HIGH TEMPERATURE
RTV SILICONE ADHESIVE/SEALANT

Page: 6

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: Shelf life - 12 months

This product is ROHS compliant.

Phrases used in s.2 and s.3: H314: Causes severe skin burns and eye damage.

R14: Reacts violently with water.

R34: Causes burns.

R36/38: Irritating to eyes and skin.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.