



## SAFETY DATA SHEET

Ltd CERAMIX TC CAULKING - HIGH TEMPERATURE ADHESIVE

Page: 1

Compilation date: 23/05/2018

Revision date: 23/05/2018

Revision No: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** CERAMIX TC CAULKING - HIGH TEMPERATURE ADHESIVE

**CAS number:** Mixture

**EINECS number:** Mixture

**Product code:** FF120 FF121

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC1: Adhesives, sealants. PROC21: Low energy manipulation of substances bound in materials and/or articles ERC5: Industrial use resulting in inclusion into or onto a matrix

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** Minkon Ltd  
Tofts Farm Industrial Estate  
Brenda Road  
Hartlepool  
UK  
TS25 2BS  
United Kingdom

**Tel:** +44 (0) 1429 273 252

**Fax:** +44 (0) 1429 232 611

**Email:** [enquiries@minkon.co.uk](mailto:enquiries@minkon.co.uk)

#### 1.4. Emergency telephone number

**Emergency tel:** +441429273252 MTWT:08:30-17:00 F:08:30-14:00  
(office hours only)

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CLP:** This product has no classification under CLP.

#### 2.2. Label elements

##### Label elements:

**Precautionary statements:** P262: Do not get in eyes, on skin, or on clothing.

P280: Wear eye protection.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

[cont...]

# SAFETY DATA SHEET

CERAMIX TC CAULKING - HIGH TEMPERATURE ADHESIVE

Page: 2

## 2.3. Other hazards

**Other hazards:** Alkaline Solution. Irritating to eyes. Irritating to skin.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Non-classified ingredients:

RAW MATERIAL - REFRACTORY ADHESIVE FILLER

EINECS	CAS	PBT / WEL	CLP Classification	Percent
Mixture	Mixture	-	-	50-70%

**Contains:** Alkaline Silicate Glass Solution.

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water.

**Eye contact:** Remove contact lenses In case of eye contact flush abundantly with water; have eye bath available. Do not rub eyes. Bathe the eye with running water for 15 minutes.

**Ingestion:** Wash out mouth with water.

**Inhalation:** Not applicable.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** The eyes may water profusely. There may be irritation and pain.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** Not applicable.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Not applicable.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

[cont...]

# SAFETY DATA SHEET

CERAMIX TC CAULKING - HIGH TEMPERATURE ADHESIVE

Page: 3

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Wash the spillage site with large amounts of water.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area.

**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

**Specific end use(s):** PC1: Adhesives, sealants.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Workplace exposure limits:** No data available.

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure good work practices. Wash splashes immediately. DO NOT eat, drink or smoke in the workplace.

**Respiratory protection:** Respiratory protection not required.

**Hand protection:** Protective gloves.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

## Section 9: Physical and chemical properties

[cont...]

# SAFETY DATA SHEET

CERAMIX TC CAULKING - HIGH TEMPERATURE ADHESIVE

Page: 4

## 9.1. Information on basic physical and chemical properties

**State:** Paste  
**Colour:** White or Black  
**Odour:** Odourless  
**Evaporation rate:** Slow  
**Oxidising:** Non-oxidising (by EC criteria)  
**Solubility in water:** Binder soluble in water/filler insoluble  
**Viscosity:** Viscous  
**Relative density:** 1.5-2.5 **pH:** >11.0  
**VOC g/l:** 0

## 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Product is stable under normal temperature and storage conditions

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** Not applicable.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Toxicity values:

Route	Species	Test	Value	Units
ORL	RAT	LD50	1600-3200	mg/kg

### Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

[cont...]

# SAFETY DATA SHEET

CERAMIX TC CAULKING - HIGH TEMPERATURE ADHESIVE

Page: 5

**Eye contact:** The eyes may water profusely. There may be irritation and pain.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** Not applicable.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Not applicable.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Disposal of packaging:** Contaminated containers must be completely emptied. Dispose of as normal industrial waste.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

**Transport class:** This product does not require a classification for transport.

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

[cont...]

## SAFETY DATA SHEET

CERAMIX TC CAULKING - HIGH TEMPERATURE ADHESIVE

Page: 6

### Section 16: Other information

#### Other information

**Other information:** All the alkali silicates, even those that are not classified as Dangerous Substances, are alkaline chemicals. Therefore contact with eyes, skin and clothes should be avoided and the usual procedures for handling all chemicals should be followed.

This product is a water based adhesive cement - VOC Content 0 gram/litre

Shelf life - 12 months

This product is ROHS compliant.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.