

# Ltd. AUTOSTIC ADHESIUM - MACHINE MOUNTING COMPOUND

Page: 1

Compilation date: 23/05/2018

**Revision date: 21/02/2020** 

**Revision No: 2** 

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: AUTOSTIC ADHESIUM - MACHINE MOUNTING COMPOUND

CAS number: Mixture
EINECS number: Mixture
Product code: FF152

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants. PROC21: Low energy manipulation of substances bound in

materials and/or articles ERC5: Industrial use resulting in inclusion into or onto a matrix

#### 1.3. Details of the supplier of the safety data sheet

Company name: Minkon Ltd

Tofts Farm Industrial Estate

Brenda Road Hartlepool TS25 2BS

UNITED KINGDOM

Tel: +44 (0) 1429 273 252
Email: enquiries@minkon.co.uk

## 1.4. Emergency telephone number

Emergency tel: MTWT:08.30-17.00 F:08.30-14.00

(office hours only)

#### Section 2: Hazards identification

## 2.1. Classification of the substance or mixture

Classification under CLP: This product has no classification under CLP.

#### 2.2. Label elements

## Label elements:

Precautionary statements: P102: Keep out of reach of children.

P103: Read label before use.

P264: Wash hands thoroughly after handling.

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

## AUTOSTIC ADHESIUM - MACHINE MOUNTING COMPOUND

Page: 2

#### 2.3. Other hazards

Other hazards: All the alkali silicates, even those that are not classified as Dangerous Substances, are

alkaline chemicals. Therefore contact with eyes, skin and clothes should be avoided and the

usual procedures for handling all chemicals should be followed.

PBT: This product is not identified as a PBT/vPvB substance.

#### Section 3: Composition/information on ingredients

#### 3.2. Mixtures

Contains: Alkaline Silicate Glass Solution.

#### Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water.

Eye contact: Remove contact lenses Bathe the eye with running water for 15 minutes. In case of eye

contact flush abundantly with water; have eye bath available. Do not rub eyes. Seek medical

attention if irritation persists

Ingestion: Wash out mouth with water.

Inhalation: Not applicable.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** The eyes may water profusely. There may be irritation and pain.

**Ingestion:** There may be irritation of the throat.

Inhalation: Not applicable.

# 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

#### Section 5: Fire-fighting measures

# 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool

containers.

## 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Not applicable.

# 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with

skin and eyes.

#### Section 6: Accidental release measures

## AUTOSTIC ADHESIUM - MACHINE MOUNTING COMPOUND

Page: 3

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up

to prevent the escape of liquid.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

## 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal

by an appropriate method.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

#### Section 7: Handling and storage

## 7.1. Precautions for safe handling

**Handling requirements:** Avoid the formation or spread of mists in the air.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

## 7.3. Specific end use(s)

Specific end use(s): PC1: Adhesives, sealants.

# Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

Workplace exposure limits: No data available.

#### **DNEL/PNEC Values**

# **AUTOSTIC ADHESIUM - MACHINE MOUNTING COMPOUND**

Туре	Exposure	Value	Population	Effect
DNEL	Oral	0.80 mg/kg bw/d	Consumers	Systemic
DNEL	Dermal	1.59 mg/kg bw/d	Workers	Systemic
DNEL	Dermal	0.80 mg/kg bw/d	Consumers	Systemic
PNEC	Fresh water	7.5 mg/l	-	-
PNEC	Marine water	1.0 mg/l	-	-
PNEC	Microorganisms in sewage treatment	348 mg/l	-	-

#### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

## AUTOSTIC ADHESIUM - MACHINE MOUNTING COMPOUND

Page: 4

**Eye protection:** Ensure eye bath is to hand. Tightly fitting safety goggles.

Skin protection: Protective clothing.

Environmental: Ensure all engineering measures mentioned in section 7 of SDS are in place.

### Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Odourless

Solubility in water: Soluble

Viscosity: Viscous

Boiling point/range°C: 100 Relative density: 1.45

pH: 11 VOC g/l: Not applicable.

#### 9.2. Other information

Other information: No data available.

# Section 10: Stability and reactivity

#### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

# 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

# 10.4. Conditions to avoid

Conditions to avoid: Product is stable under normal temperature and storage conditions

#### 10.5. Incompatible materials

Materials to avoid: As supplied (i.e. the adhesive is in liquid form) - the product contains a water based alkaline

binder, and the wet adhesive will react readily with acids. After full cure - the product is highly

stable (high temperature resistant and non-reactive).

# 10.6. Hazardous decomposition products

Haz. decomp. products: Not applicable.

# **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

## AUTOSTIC ADHESIUM - MACHINE MOUNTING COMPOUND

Page: 5

## **Toxicity values:**

Route	Species	Test	Value	Units
ORAL	RAT	LD50	1600-3200	mg/kg
ORL	RAT	LD50	1600-3200	mg/kg

#### Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** The eyes may water profusely. There may be irritation and pain.

**Ingestion:** There may be irritation of the throat.

Inhalation: Not applicable.

# **Section 12: Ecological information**

## 12.1. Toxicity

## **Ecotoxicity values:**

Species	Test	Value	Units
ZEBRAFISH (Brachydanio rerio)	96H LC50	1108	mg/l
Daphnia magna	48H EC50	1700	mg/l

## 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

# 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

#### 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

#### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

Disposal operations: Dispose of waste in accordance with local authority requirements.

Disposal of packaging: Contaminated containers must be completely emptied. Dispose of as normal industrial

waste.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

## AUTOSTIC ADHESIUM - MACHINE MOUNTING COMPOUND

Page: 6

#### **Section 14: Transport information**

**Transport class:** This product does not require a classification for transport.

#### **Section 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

#### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by

the supplier.

#### **Section 16: Other information**

#### Other information

Other information: All the alkali silicates, even those that are not classified as Dangerous Substances, are

alkaline chemicals. Therefore contact with eyes, skin and clothes should be avoided and the

usual procedures for handling all chemicals should be followed.

Shelf life for tins - 12 months.

This product is ROHS compliant.

REACH1 - Minkon UK Ltd is a formulator and blender of substances. Raw materials supplied

us are expected to be supported by the REACH legislation where required.

REACH2 - This product contains no Substances of Very High Concern as listed at:

http://echa.europa.eu/web/guest/candidate-list-table

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and

shall be used only as a guide. This company shall not be held liable for any damage resulting

from handling or from contact with the above product.