

DATA SHEET

Fortafix High Temperature Adhesives

FORTAFIX – Premium Stove Rope Kit

FORTAFIX Premium Stove Rope Kit - Use to provide a durable and resilient gas tight seal, around the door closure of wood-burning & multi-fuel stoves.

- Suitable for solid fuel stoves and boilers
- Flexseal adhesive will produce a tough durable long life seal
 - Will bond to glass, ceramic rope, painted & unpainted metal surfaces
- U.K. manufactured high quality glass fibre rope

The kit comprises:

- Durable high temperature resisting flexible silicone adhesive sealant
 - o Temperature rated to 300°C
 - Supplied as an 80 ml squeezable tube
- 2 metres of U.K. manufactured high quality glass fibre rope
 - o A range of diameters 6mm 8mm 10mm 12mm.
- High temperature resisting 'end seal' tape
- Protective gloves

Directions for Use:

- 1.0 Use gloves supplied
- 2.0 Remove the door from the stove and lay flat
- 3.0 Remove and clean away old rope and adhesive.
- 4.0 Cut nozzle on adhesive and apply adhesive bead into the stove door recess
 - 4.1 Starting in centre of straight section of channel apply the rope around channel and press into place.
 - 4.2 When rope ends meet, apply fibre tape supplied around rope prior to cutting to length.
 - 4.3 Press two butt ends firmly into place.
- 5.0 Reattach the door and close to apply pressure to the new rope
- 6.0 Allow 24 hours for adhesive to cure before lighting stove
 - 6.1 Adhesive will produce a light acetic acid smell during initial curing

Health and Safety / Environmental Information

- See separate MSDS sheet copy available on website
- RoHS Compliant.

Storage

■ Shelf life – 12 months.

Web: www.minkon.co.uk www.fortafix.com