

FORTAFIX HT FLUESEAL - HIGH TEMPERATURE FLUE SEALANT

Page: 1

Compilation date: 24/05/2018

Revision date: 04/03/2020

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: FORTAFIX HT FLUESEAL - HIGH TEMPERATURE FLUE SEALANT

CAS number: Mixture
EINECS number: Mixture
Product code: FF114

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants. PROC21: Low energy manipulation of substances bound in

materials and/or articles ERC5: Industrial use resulting in inclusion into or onto a matrix

1.3. Details of the supplier of the safety data sheet

Company name: Minkon Ltd

Tofts Farm Industrial Estate

Brenda Road Hartlepool TS25 2BS

UNITED KINGDOM

Tel: +44 (0) 1429 273 252
Email: enquiries@minkon.co.uk

1.4. Emergency telephone number

Emergency tel: MTWT:08.30-17.00 F:08.30-14.00

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: This product has no classification under CLP.

2.2. Label elements

Label elements:

Precautionary statements: P262: Do not get in eyes, on skin, or on clothing.

P280: Wear eye protection.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

FORTAFIX HT FLUESEAL - HIGH TEMPERATURE FLUE SEALANT

Page: 2

2.3. Other hazards

Other hazards: Alkaline Solution. Irritating to eyes. Irritating to skin. All the alkali silicates, even those that are

not classified as Dangerous Substances, are alkaline chemicals. Therefore contact with

eyes, skin and clothes should be avoided and the usual procedures for handling all chemicals

should be followed.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Contains: Alkaline Silicate Glass Solution.

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Remove contact lenses Bathe the eye with running water for 15 minutes. In case of eye

contact flush abundantly with water; have eye bath available. Do not rub eyes. Seek medical

attention if irritation persists

Ingestion: Wash out mouth with water.

Inhalation: Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: The eyes may water profusely. There may be irritation and pain.

Ingestion: There may be irritation of the throat.

Inhalation: Not applicable.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool

containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Not applicable.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with

skin and eyes.

FORTAFIX HT FLUESEAL - HIGH TEMPERATURE FLUE SEALANT

Page: 3

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Wear Suitable Eye Protection.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Wash the spillage site with large amounts of water.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the

air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area.Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): PC1: Adhesives, sealants.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure good work practices. Wash splashes

immediately. DO NOT eat, drink or smoke in the workplace.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves. Gloves (alkali-resistant).

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

FORTAFIX HT FLUESEAL - HIGH TEMPERATURE FLUE SEALANT

Page: 4

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Dark greyOdourless

Evaporation rate: Slow

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Binder soluble in water/filler insoluble

Viscosity: Viscous

Boiling point/range°C: 100 Relative density: 1.5-2.5

pH: >11.0 **VOC g/l**: 0

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Product is stable under normal temperature and storage conditions

10.5. Incompatible materials

Materials to avoid: As supplied (i.e. the adhesive is in liquid form) - the product contains a water based alkaline

binder, and the wet adhesive will react readily with acids. After full cure - the product is highly

stable (high temperature resistant and non-reactive).

10.6. Hazardous decomposition products

Haz. decomp. products: Not applicable.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

| . | ^ · | | | 11 % |
|----------|------------|------|---------|-------|
| Route | Species | Lest | ∟ Value | Units |
| | | | | |

FORTAFIX HT FLUESEAL - HIGH TEMPERATURE FLUE SEALANT

Page: 5

ORL RAT LD50 1600-3200 mg/kg

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: The eyes may water profusely. There may be irritation and pain.

Ingestion: There may be irritation of the throat.

Inhalation: Not applicable.

Other information: Ensure eye bath is to hand

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Only slightly biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Not applicable.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Dispose of waste in accordance with local authority requirements.

Disposal of packaging: Contaminated containers must be completely emptied. Dispose of as normal industrial

waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

FORTAFIX HT FLUESEAL - HIGH TEMPERATURE FLUE SEALANT

Page: 6

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: All the alkali silicates, even those that are not classified as Dangerous Substances, are

alkaline chemicals. Therefore contact with eyes, skin and clothes should be avoided and the

usual procedures for handling all chemicals should be followed.

This product is a water based adhesive cement - VOC Content 0 gram/litre

Shelf life - 12 months

This product is ROHS compliant.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and

shall be used only as a guide. This company shall not be held liable for any damage resulting

from handling or from contact with the above product.