

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** FORTAFIX U529NH - HIGH TEMPERATURE STRAIN GAUGE CEMENT

**CAS number:** Mixture

**EINECS number:** Mixture

**Product code:** FF153

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** PC1: Adhesives, sealants. PROC21: Low energy manipulation of substances bound in materials and/or articles ERC5: Industrial use resulting in inclusion into or onto a matrix

**1.3. Details of the supplier of the safety data sheet**

**Company name:** Minkon Ltd  
Tofts Farm Industrial Estate  
Brenda Road  
Hartlepool  
TS25 2BS  
UNITED KINGDOM

**Tel:** +44 (0) 1429 273 252

**Email:** [enquiries@minkon.co.uk](mailto:enquiries@minkon.co.uk)

**1.4. Emergency telephone number**

**Emergency tel:** MTWT:08.30-17.00 F:08.30-14.00  
(office hours only)

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CLP:** Eye Dam. 1: H318; Skin Irrit. 2: H315

**Most important adverse effects:** Causes skin irritation. Causes serious eye damage.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** H315: Causes skin irritation.

H318: Causes serious eye damage.

**Hazard pictograms:** GHS05: Corrosion



# SAFETY DATA SHEET

FORTAFIX U529NH - HIGH TEMPERATURE STRAIN GAUGE CEMENT

Page: 2

**Signal words:** Danger

**Precautionary statements:** P102: Keep out of reach of children.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call POISON CENTER/doctor.

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

RAW MATERIAL - MONO ALUMINIUM PHOSPHATE SOLUTION - REACH registered number(s): 2119490078-32-0000

EINECS	CAS	PBT / WEL	CLP Classification	Percent
236-875-2	13530-50-2	-	Eye Dam. 1: H318	30-50%

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

[cont...]

# SAFETY DATA SHEET

FORTAFIX U529NH - HIGH TEMPERATURE STRAIN GAUGE CEMENT

Page: 3

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Corrosive.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** Must only be kept in original packaging. Glass.

### 7.3. Specific end use(s)

**Specific end use(s):** PC1: Adhesives, sealants.

## Section 8: Exposure controls/personal protection

[cont...]

# SAFETY DATA SHEET

FORTAFIX U529NH - HIGH TEMPERATURE STRAIN GAUGE CEMENT

Page: 4

## 8.1. Control parameters

**Workplace exposure limits:** No data available.

## DNEL/PNEC Values

**Hazardous ingredients:**

### RAW MATERIAL - MONO ALUMINIUM PHOSPHATE SOLUTION

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	4.07 mg/m <sup>3</sup>	Workers	Systemic
DNEL	Inhalation	3.04 mg/m <sup>3</sup>	Consumers	Systemic
PNEC	Fresh water	0.032725 mg/l	-	-
PNEC	Marine water	0.003273 mg/l	-	-

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** White

**Odour:** Odourless

**Evaporation rate:** Negligible

**Oxidising:** Non-oxidising (by EC criteria)

**Solubility in water:** Miscible in all proportions

**Viscosity:** Viscous

**VOC g/l:** 0

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

[cont...]

# SAFETY DATA SHEET

FORTAFIX U529NH - HIGH TEMPERATURE STRAIN GAUGE CEMENT

Page: 5

## 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

**Conditions to avoid:** Product is stable under normal temperature and storage conditions

## 10.5. Incompatible materials

**Materials to avoid:** Bases.

## 10.6. Hazardous decomposition products

**Haz. decomp. products:** Not applicable.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Hazardous ingredients:**

#### RAW MATERIAL - MONO ALUMINIUM PHOSPHATE SOLUTION

DERMAL	RBT	LD50	>4640	mg/kg
DUST/MIST	RAT	4H LC50	>5.1	mg/l
ORAL	RAT	LD50	>2000	mg/kg

**Relevant hazards for product:**

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain.  
The vision may become blurred. May cause permanent damage.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

**Hazardous ingredients:**

[cont...]

# SAFETY DATA SHEET

FORTAFIX U529NH - HIGH TEMPERATURE STRAIN GAUGE CEMENT

Page: 6

## RAW MATERIAL - MONO ALUMINIUM PHOSPHATE SOLUTION

Daphnia magna	48H EC50	>100	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	>100	mg/l

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Disposal of packaging:** Contaminated containers must be completely emptied. Dispose of in accordance with local authority requirements.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

**Transport class:** This product does not require a classification for transport.

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

[cont...]

## SAFETY DATA SHEET

FORTAFIX U529NH - HIGH TEMPERATURE STRAIN GAUGE CEMENT

Page: 7

**Phrases used in s.2 and s.3:** H315: Causes skin irritation.

H318: Causes serious eye damage.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.