

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form	: Mixture
Trade name	: Fortafix Ceramix TC Caulking Compound Black
Product code	: FFM120
Type of product	: adhesives
Product group	: End product

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Intended for general public	
Main use category	: Industrial use, Professional use, Consumer use
Industrial/Professional use spec	: Industrial
Use of the substance/mixture	: Adhesives, binding agents
Function or use category	: Flame retardants and fire preventing agents

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Minkon Ltd  
Tofts Farm Industrial Estate  
Brenda Road  
TS25 2BS Hartlepool – Durham  
United Kingdom  
T 01429 273252  
[sales@minkon.co.uk](mailto:sales@minkon.co.uk) - [www.minkon.co.uk](http://www.minkon.co.uk)

**1.4. Emergency telephone number**

Emergency number : ++44 (0)1429 273252

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Not classified

**Adverse physicochemical, human health and environmental effects**

Causes eye irritation. Causes mild skin irritation. May be harmful if swallowed. May cause an allergic skin reaction.

**2.2. Label elements**

According to EC directives or the corresponding national regulations there is no labelling obligation for this product.  
No labelling applicable

**2.3. Other hazards**

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

**SECTION 3: Composition/information on ingredients****3.1. Substances**

Not applicable

# Fortafix Ceramix TC Caulking Compound Black

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 3.2. Mixtures

Comments : Additives

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
QUARTZ substance with national workplace exposure limit(s) (AT, BE, DK, EE, ES, FI, FR, HR, IE, LT, NL, PL, PT, SE, SK)	CAS-No.: 14808-60-7 EC-No.: 238-878-4	20 – 30	STOT RE 2, H373
sodium silicate	CAS-No.: 1344-09-8 EC-No.: 215-687-4 REACH-no: 01-211944872531	< 20	Skin Corr. 1, H314 Eye Dam. 1, H318

Comments : Additives

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : If medical advice is needed, have product container or label at hand.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.  
First-aid measures after skin contact : Wash skin with plenty of water.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Causes serious eye irritation. May cause an allergic skin reaction.  
Symptoms/effects after inhalation : None under normal use.  
Symptoms/effects after skin contact : Causes skin irritation. Prolonged or repeated contact may cause skin to become dry.  
Symptoms/effects after eye contact : Causes eye irritation. redness, itching, tears.  
Symptoms/effects after ingestion : May be harmful if swallowed.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Not flammable. No fire hazard.  
Explosion hazard : No direct explosion hazard.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

# Fortafix Ceramix TC Caulking Compound Black

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth.  
Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

#### 7.3. Specific end use(s)

Adhesives, Sealants.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

QUARTZ (14808-60-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Silica crystalline (Quartz)
Remark	(Year of adoption 2003)
Regulatory reference	SCOEL Recommendations
Austria - Occupational Exposure Limits	
Local name	Quarzfeinstaub (alveolengängiges kristallines Siliziumdioxid)
MAK (OEL TWA)	0.05 mg/m <sup>3</sup> (A)
Remark	Krebserzeugend: III C
Regulatory reference	BGBl. II Nr. 156/2021

# Fortafix Ceramix TC Caulking Compound Black

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>QUARTZ (14808-60-7)</b>	
<b>Austria - Biological limit values</b>	
Local name	Quarz Staub
Remark	<p>Eignung mit vorzeitiger Folgeuntersuchung: Bei Vorliegen einer wesentlichen Beeinträchtigung der Lungenfunktion. Diese liegt jedenfalls vor, wenn nach mehrmaliger Messung der beste gemessene Wert den für den/die Untersuchte/n maßgebenden Sollwert um 20% unterschreitet bzw. den MEF50-Sollwert um 50% unterschreitet. Eine vorzeitige Folgeuntersuchung ist jedoch nicht erforderlich, wenn im Vergleich zu Vorbefunden der altersabhängige physiologische Abfall der 1-Sekundenkapazität (FEV1) von 40 ml/Jahr nicht überschritten wird oder aus der Beurteilung des Kurvenverlaufes der Forcierten Vitalkapazität (FVC) eine eingeschränkte Mitarbeit des Untersuchten/der Untersuchten ersichtlich ist.</p> <p>Der Zeitabstand zwischen den Untersuchungen beträgt bei Eignung: zwei Jahre bzw. für die Röntgenuntersuchung 4 Jahre; bei Eignung mit vorzeitiger Folgeuntersuchung: ein Jahr. Sofern eine vorzeitige Folgeuntersuchung lediglich auf Grund veränderter Lungenfunktionswerte erfolgt, ist die Lungenfunktionsprüfung durchzuführen, jedoch keine Röntgen-Aufnahme anzufertigen.</p>
Regulatory reference	Verordnung über die Gesundheitsüberwachung am Arbeitsplatz 2017 (VGÜ 2017)
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Silices cristallines: quartz (poussières alvéolaires) # Siliciumdioxide (kristallijn): kwarts (inadembaar stof)
OEL TWA	0.1 mg/m <sup>3</sup>
Remark	<p>C: la mention "C" signifie que l'agent en question relève du champ d'application du titre 2 relatif aux agents cancérigènes, mutagènes et reprotoïques du livre VI du code de bien-être au travail. # C: de vermelding "C" betekent dat het betrokken agens valt onder het toepassingsgebied van titel 2 betreffende kankerverwekkende, mutagene en reprotoxische agentia van boek VI van de codex over het welzijn op het werk.</p>
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020
<b>Croatia - Occupational Exposure Limits</b>	
Local name	Kristalni SiO <sub>2</sub> , kvarc
GVI (OEL TWA) [1]	0.1 mg/m <sup>3</sup>
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 1/2021)
<b>Denmark - Occupational Exposure Limits</b>	
Local name	Kvarts
OEL TWA [1]	0.1 mg/m <sup>3</sup> total, respirabel 0.3 mg/m <sup>3</sup> total
Remark	E (betyder, at stoffet har en EF-grænseværdi); K (betyder, at stoffet anses for at kunne være kræftfremkaldende)
Regulatory reference	BEK nr 1426 af 28. juni 2021
<b>Estonia - Occupational Exposure Limits</b>	
Local name	Kvarts
OEL TWA	0.1 mg/m <sup>3</sup> peentolm
Remark	1 (Peentolm koosneb alla 2,5-mikromeetrise läbimõõduga osakestest, mis võivad jõuda koos sissehingatava õhuga kopsu alveoolidesse (respireeritav fraktsioon)), C (Kantserogeenne aine)
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 17.10.2019, 2); Vabariigi Valitsuse 10. märtsi 2019. a määruse nr 84

# Fortafix Ceramix TC Caulking Compound Black

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>QUARTZ (14808-60-7)</b>	
<b>Finland - Occupational Exposure Limits</b>	
Local name	Kvartsi
HTP (OEL TWA) [1]	0.05 mg/m <sup>3</sup> alveolijae
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
<b>France - Occupational Exposure Limits</b>	
Local name	Silice (poussières alvéolaires de quartz)
VME (OEL TWA)	0.1 mg/m <sup>3</sup>
Remark	Valeurs réglementaires contraignantes
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n°2021-434)
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Quartz, respirable dust
OEL TWA [1]	0.1 mg/m <sup>3</sup>
Remark	BOELV (Binding Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
<b>Lithuania - Occupational Exposure Limits</b>	
Local name	Kvarcas, silicio dioksido atmaina
IPRV (OEL TWA)	0.1 mg/m <sup>3</sup> (alveolinė frakcija)
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
<b>Netherlands - Occupational Exposure Limits</b>	
Local name	Respirabel kristallijn silicastof: – kwarts
TGG-8u (OEL TWA)	0.075 mg/m <sup>3</sup> Respirabele fractie
Remark	Kankerverwekkende stof
Regulatory reference	Arbeidsomstandighedenregeling 2021
<b>Poland - Occupational Exposure Limits</b>	
Local name	Krzemionka krystaliczna – kwarc
NDS (OEL TWA)	0.1 mg/m <sup>3</sup> frakcja respirabilna
Remark	Frakcja respirabilna – frakcja aerozolu wnikająca do dróg oddechowych, która stwarza zagrożenie dla zdrowia po zdeponowaniu w obszarze wymiany gazowej.
Regulatory reference	Dz. U. 2018 poz. 1286
<b>Portugal - Occupational Exposure Limits</b>	
Local name	Silica, cristalina α-Quartzo
OEL TWA	0.025 mg/m <sup>3</sup> R (Fração respirável)
Remark	A2 (Agente carcinogénico confirmado nos animais de laboratorio con relevância desconhecida no Homem)
Regulatory reference	Norma Portuguesa NP 1796:2014
<b>Slovakia - Occupational Exposure Limits</b>	
Local name	Oxid kremičitý, kryštalicový
NPHV (OEL TWA) [1]	0.1 mg/m <sup>3</sup> respirabilná frakcia (TSH)
Remark	Kategória karcinogénov 1A – Dokázaný karcinogén pre ľudí

# Fortafix Ceramix TC Caulking Compound Black

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>QUARTZ (14808-60-7)</b>	
Regulatory reference	Nariadenie vlády č. 356/2006 Z. z. (235/2020 Z. z.)
<b>Spain - Occupational Exposure Limits</b>	
Local name	Sílice Cristalina: Cuarzo
VLA-ED (OEL TWA) [1]	0.1 mg/m <sup>3</sup> Fracción respirable 0.05 mg/m <sup>3</sup> Fracción respirable. Entrada en vigor en enero de 2022
Remark	v (Agente cancerígeno con valor límite vinculante recogido en el anexo III del Real Decreto 665/1997 y en sus modificaciones posteriores), d (Véase UNE EN 481: Atmósferas en los puestos de trabajo. Definición de las fracciones por el tamaño de las partículas para la medición de aerosoles), y (Reclasificado, por la International Agency for Research on Cancer (IARC) de grupo 2A (probablemente carcinogénico en humanos) a grupo 1 (carcinogénico en humanos)).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
<b>Sweden - Occupational Exposure Limits</b>	
Local name	Kvarts
NGV (OEL TWA)	0.1 mg/m <sup>3</sup> respirabel fraktion; Se även: Kristobalit och Tridymit
Remark	C (Ämnet är cancerframkallande. Risk för cancer finns även vid annan exponering än via inandning. För vissa cancerframkallande ämnen som inte har gränsvärden gäller förbud eller tillståndskrav enligt föreskrifterna om kemiska arbetsmiljörisker); M (Medicinska kontroller kan krävas för hantering av ämnet. Se vidare föreskrifterna om medicinska kontroller i arbetslivet. För vissa ämnen ska arbetsgivaren erbjuda läkarundersökning och för andra ämnen gäller krav på periodisk läkarundersökning och tjänstbarhetsbedömning); 3 (Den respirabla fraktionen är de inhalerbara partiklar som når längst ner i luftvägarna, till alveolerna i lungorna)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
<b>Norway - Occupational Exposure Limits</b>	
Local name	Krystallinsk silika (SiO <sub>2</sub> ), α-kvarts
Grenseverdi (OEL TWA) [1]	0.3 mg/m <sup>3</sup> Totalstøv 0.1 mg/m <sup>3</sup> Respirabelt støv
Remark	K: Kjemikalier som skal betraktes som kreftfremkallende; G: EU har fastsatt en bindende grenseverdi og/eller anmerkning for stoffet; 7) Støv som inneholder α-kvarts, kristobalitt og/eller tridymitt vurderes ut fra summasjonsformel. Samtidig må verdiene for sjenerende støv overholdes.
Regulatory reference	FOR-2021-06-28-2248
<b>North Macedonia - Occupational Exposure Limits</b>	
Local name	силика (кремен)
OEL TWA	0.15 mg/m <sup>3</sup> (A) алвеоларна фракција – дел на вдишани суспендирани материји, кои доспеваат до алвеолите
Remark	(Y)
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)
<b>Switzerland - Occupational Exposure Limits</b>	
Local name	Dioxyde de silicium cristallisé [Quartz, Cristobalite, Tridymite] / Siliciumdioxid, kristallin [Quarz, Tridymit, Cristobalit]
MAK (OEL TWA) [1]	0.15 mg/m <sup>3</sup> (a) / (a)
Critical toxicity	Cancpulg, Silicose / Lungenkrebs, Silikose

# Fortafix Ceramix TC Caulking Compound Black

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

QUARTZ (14808-60-7)	
Notation	C1A, SS <sub>C</sub> , P / C1A, SS <sub>C</sub> , P
Remark	HSE, NIOSH, OSHA
Regulatory reference	www.suva.ch, 01.01.2021

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Paste.
Colour	: Black.
Odour	: slight.

# Fortafix Ceramix TC Caulking Compound Black

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity (oral)	: May be harmful if swallowed (Not available)
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

sodium silicate (1344-09-8)	
LD50 dermal rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 2.06 mg/l air Animal: rat, Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
Skin corrosion/irritation	: Slightly irritant but not relevant for classification (Not available)



# Fortafix Ceramix TC Caulking Compound Black

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### sodium silicate (1344-09-8)

pH	> 13.5 Concentration: ]42 vol%,46 vol%[
----	---

Serious eye damage/irritation : Slightly irritant but not relevant for classification (Not available)

### sodium silicate (1344-09-8)

pH	> 13.5 Concentration: ]42 vol%,46 vol%[
----	---

Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified  
STOT-single exposure : Not classified  
STOT-repeated exposure : Not classified.

### QUARTZ (14808-60-7)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

Aspiration hazard : Not classified

### QUARTZ (14808-60-7)

Viscosity, kinematic	Not applicable
----------------------	----------------

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Not classified  
Not rapidly degradable

### sodium silicate (1344-09-8)

LC50 - Fish [1]	3185 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	1700 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	207 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	> 345.4 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

# Fortafix Ceramix TC Caulking Compound Black

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

#### 14.6. Special precautions for user

##### Overland transport

Not applicable

##### Transport by sea

Not applicable

##### Air transport

Not applicable

##### Inland waterway transport

Not applicable

##### Rail transport

Not applicable

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

###### REACH Annex XVII (Restriction List)

Contains no REACH substances with Annex XVII restrictions

###### REACH Annex XIV (Authorisation List)

Contains no REACH Annex XIV substances

# Fortafix Ceramix TC Caulking Compound Black

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### REACH Candidate List (SVHC)

Contains no substance on the REACH candidate list

### PIC Regulation (Prior Informed Consent)

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

### POP Regulation (Persistent Organic Pollutants)

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

### Ozone Regulation (1005/2009)

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

### Explosives Precursors Regulation (2019/1148)

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

### Drug Precursors Regulation (273/2004)

Contains no substance subject to Regulation (EC) 273/2004 of the European Parliament and of the Council of 11 February 2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances.

## 15.1.2. National regulations

### Germany

- Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).  
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
- Water hazard class (WGK) : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).
- Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

### Netherlands

- SZW-lijst van kankerverwekkende stoffen : QUARTZ is listed
- SZW-lijst van mutagene stoffen : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

### Denmark

- Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product  
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

### Switzerland

- Storage class (LK) : LK 10/12 - Liquids

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor

# Fortafix Ceramix TC Caulking Compound Black

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Abbreviations and acronyms:	
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H373	May cause damage to organs through prolonged or repeated exposure.
Skin Corr. 1	Skin corrosion/irritation, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2

# Fortafix Ceramix TC Caulking Compound Black

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

---

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.